




Standard Cable Ties

- **Material:** PA6,6, flame rating UL94V-2
- **Color:** UV Black
- **Quantity:** 100pcs/bag



Model Name	Length (L)		Width (W)		Max.Bundle ø		Min. Loop Tensile Strength		Operating Temperature		Min. Installation Temperature	
	mm	inch	mm	inch	mm	inch	kgf	lbf	° C	° F	° C	° F
100 x 2.5	100	3.94	2.5	0.1	22	0.87	8.2	18	-40 ~ 85	-40 ~ 185	-20	-4
150 x 3.6	150	5.91	3.6	0.14	35	1.38	18.2	40	-40 ~ 85	-40 ~ 185	0	32
200 x 3.6	200	7.87	3.6	0.14	53	2.09	18.2	40	-40 ~ 85	-40 ~ 185	0	32
250 x 3.6	250	9.84	3.6	0.14	65	2.56	18.2	40	-40 ~ 85	-40 ~ 185	0	32
300 x 4.8	300	11.81	4.8	0.19	76	2.99	22.6	50	-40 ~ 85	-40 ~ 185	-20	-4
300 x 3.6	300	11.81	3.6	0.14	76	2.99	18.2	40	-40 ~ 85	-40 ~ 185	-20	-4
300 x 7.6	300	11.81	7.6	0.3	76	2.99	54.5	120	-40 ~ 85	-40 ~ 185	-20	-4
390 x 7.6	390	15.35	7.6	0.3	108	4.25	54.5	120	-40 ~ 85	-40 ~ 185	-20	-4
450 x 7.6	450	17.72	7.6	0.3	130	5.12	54.5	120	-40 ~ 85	-40 ~ 185	-20	-4
550 x 7.6	533	20.98	7.6	0.3	140	5.51	54.5	120	-40 ~ 85	-40 ~ 185	-20	-4
610 x 9.0	609	23.98	9	0.35	178	7.01	79.3	175	-40 ~ 85	-40 ~ 185	-20	-4

